



GRAPHIC & CLASSIC

Properties

Our GRAPHIC and CLASSIC terracotta tiles are made from red clay. Each tile often has a unique and varied appearance, enhanced by a vibrant, crackled glaze with depth and character. The tiles are fired at high temperatures, making them suitable for walls and floors in areas with light foot traffic. They are ideal for indoor use – on floors, walls, and other clad surfaces. The tiles may emit a slight crackling sound before and after installation, caused by the glaze forming fine crackles due to temperature changes and handling. This is a natural feature of handmade tiles and is considered completely normal and to be expected.

We also offer customized solutions with glazed edges, special trims, and unique formats tailored to each project and design vision.

GRAPHIC and CLASSIC tiles may vary in size by +/- 3–5 mm depending on the type and glaze.

Installation guide

We recommend that our tiles are installed by experienced professionals to ensure the best possible result. We recommend that the installation of our tiles be carried out by experienced professionals for the best results.

- Inspect all tiles upon delivery. Do not sign off before they have been thoroughly checked.
- Protect the tiles from dust and dirt during and after installation.
- Individual tiles may need to be rotated or replaced to ensure the best result.
- Never leave acidic products or cleaners on the glazed surface, as this can cause visible discoloration.

We recommend

- Always consult a professional. We do not accept responsibility for any installation errors.
- Test grout on a sample tile to avoid staining or discoloration.
- Use minimal joint spacing for a harmonious look.
- Plan your layout carefully to evenly distribute color variations.

Ensure the substrate is clean, level, and stable. We recommend unpacking several boxes and mixing the tiles to achieve a visually balanced result.

Cutting

Tiles should be cut using a wet cutter with a diamond or granite blade and clean water, or a high-quality tile cutter. Cut slowly to avoid chipping. Tiles should be sealed before cutting, and cut edges can be finished with fine sandpaper.

Grout spacing

We recommend the smallest possible grout spacing for a clean, elegant look. However, due to variations in tile size, a minimum of 3–4 mm is often necessary. Always follow professional advice based on your specific project.

Grouting

Choose a grout color that matches the tiles. Dark grout may highlight the glaze's natural crackling. Tiles should ideally be sealed before cutting and grouting using FILA PRW200, and again after installation with FILA MP90 Eco Extreme or a similar product. Always follow the instructions provided by the product manufacturer.

Maintenance

Only use acid-free products and descaling agents, especially suitable for glazed tiles and natural stone. Never use undiluted chlorine, alcohol, acid or solvent-based cleaners and/or abrasive cleaners. Never use coarse scouring pads.

Damaged tiles should always be replaced by a professional.

Anti-slip treatment

We offer a range of solutions and production methods for anti-slip treatment. Tiles can either be treated with anti-slip products after installation to increase friction or produced with a textured, slip-resistant surface. If your project has specific anti-slip requirements, feel free to contact us to learn more about the available options.

If you have any questions, don't hesitate to reach out.